

Sony Cinealta Cinema Prime lenses SCL-PK6 (20/25/35/50/85/135 mm)/SCL-PK3 (20/25/135 mm)

Focal Length	20 mm	25mm	35 mm	50 mm	85 mm	135 mm
Minimum Object Distance (from image plane)	0.25 m (10")	0.25m (10")	0.35 mm (1'2")	.50 m (1'8")	0.85 m (2'9")	0.85 m (2'9")
Mass	2.3 kg (5lb 1 oz)	2.2 kg (4lb 14oz)	2.1 kg (4lb 10oz)	2.0 kg (4lb 7 oz)	2.0 kg (4lb 7oz)	2.4 kg (5lb 5oz)
Operating Temperatre	0°C to 40°C (32°F to 104°F)					
Storage Temperature	-20 °C to +60 °C (-4 °F to +140 °F)					
T-Stop Range	T2 to T22					
Flange back	52 mm (in air)					
Focus Rotation	240°					
Number of aperture blades	9					
Filter mounting screw	M 95 mm, pitch 1.0 mm (excluding 20 mm)					
Mount system	PL mount					

Specifications are provided for the informational use of our clients and are taken from sources deemed to be reliable, but not guaranteed. Exact specifications may vary due to issues such as firmware or version. Please check with the team at Triode regarding any mission critical specifications before renting any equipment. <https://triode.tv/contact/> or call 717-455-3940.